


RF-GENERATOR

13.56 MHz, 300 W

diener^{electronic}
Plasma-Surface-Technology



RF-GENERATOR

electronic
diener

Plasma-Surface-Technology

- Rated RF power output: 300 Watts
- Frequency: 13.560 MHz $\pm$ 100ppm
- Adjustable RF power range:
0 – 300 Watts, continuous
- Generator can be pulsed:
Min. on-time: 5 μ s
- Impedance: 50 Ohms
- RF stability: less than 5 %
- Load mismatch protection (built-in)
against open output and short circuit
- Regulation tolerance load:
VSWR = 1,2
- Capable of switching power to 100% immediately
- Mains input: 88 - 264 VAC / 47 – 63 Hz
- Mains power consumption: max 580 Watts
- Remote interface connector intended for:
 - RF switch ON/OFF
 - RF power adjustment (0...10V $\hat{=}$ 0...100%)
- RF output: N connector
- Power connector: for external power supply
- Weight: approx. 18 kg (generator)
- 19-inch rack

Applications:


- Low pressure plasma
- Dielectric heating



pic: front view



pic: rear view



19-inch rack

Please visit our homepage at:

www.plasma.de

Diener electronic GmbH + Co. KG
Nagolder Str. 61
72224 Ebhausen / Germany

Telephone: +49 (0) 7458 / 999 31 - 0
Telefax: +49 (0) 7458 / 999 31 - 50
E-Mail: info@plasma.de